

BB15 & BB25 Series

Features	Benefits
Heavy side panels	5-16" & 3/8" (8 & 10 mm) Built heavy to handle the tough jobs.
Square tubing shank support	Many competitors use angle iron. Box tubing is stronger.
Clevis -type lower 3-point hitch	Much stronger than pin type hitch.
4 Position heat treated spring steel shanks	Offers flexibility for deep to shallow settings and Heat-treated for longevity.
Working widths	15 Series: 60", 66" & 72" (152, 168, & 183 cm) 25 Series: 60", 66", 72", 84" & 96" (152, 168, 183, 213, & 244 cm)
horsepower Range	15 Series: 17-40 horsepower (13-30 kW) 25 Series: 25-55 horsepower (19-41 kW)
Roll-formed moldboard	Roll-formed moldboard keeps materials flowing which puts less drag on the Box Scraper, resulting in lower horsepower requirements and faster working conditions.
17" (43 cm) Moldboard height	High material capacity.
Moldboard	Heavy moldboard with precise roll holds its shape under heavy loads.
Heat treated dimpled-on tips	Easy to replace tips that are heat treated for toughness.
Heat-treated, reversible, and replaceable cutting blades	Heat-treated for hardness. Reversible so both edges can be used before replacing the cutting blades.
Rear backfill blade	Rear backfill blade allows for backfilling trenches or foundations.
Warranty	One year parts and labor.
Category 1 3-point hitch with Quick Hitch capability	Fits a wide variety of tractors. Quick Hitch capability allows for easy hook-up.
Heavy 4" x 4" X 5/16" front beam with 5/16" x 1" shank hole reinforcement	Reinforcement adds additional strength to shank tube right behind shank where maximum pressure is applied.
Strong Bucket Reinforcement BB15Series BB25 Series	Two welded braces extending from front to rear of bucket help keep the Box Scraper square under heavy loads. Two welded braces extending from front to rear of bucket plus welded gussets between the side panels and moldboard provide exceptional strength for keeping the Box Scraper square under heavy loads.